

Model Number	DA0913-H120	DA1213-H120	DA1813-H230	DA2413-H230
Power Supply (V/Ph/Hz)	110-120/1/60	110-120/1/60	208-230/1/60	208-230/1/60
Capacity (Btu/h) Cooling	9000	12000	18000	24000
Heating	9000	12000	18000	24000
SEER	13	13	13	13
HSPF	8	8	8	7.7
EER	12	12	12	11
Dehumidification (Pts/Hr)	1.58	2.11	2.99	4.4
Current (A) Rated/Max Cooling	7.2/10.2	9.6/13.1	6.5/8.6	8.5/10.2
Heating	6.8/9.64	9.3/12.3	6.4/8.6	8/9.9
Power Consumption (kW) Rated/Max Cooling	0.77/1.12	1.01/1.42	1.48/1.85	1.93/2.21
Heating	0.72/1.05	1/1.35	1.48/1.85	1.8/2.14
Indoor Air Circulation: L / M / H (CFM)	223/276/330	276/330/376	500/553/618	612/665/724
Indoor Noise Level dB(A): L / M / H	42/38/35	42/38/35	50/47/44	50/47/44
Outdoor Fan Speed (RPM)	910	790	780	780
Outdoor Noise Level dB(A)	~55	~55	~60	~59
Indoor Fan Speeds	1250/1100/950	1250/1100/950	1220/1100/1000	1220/1100/1000
Connection Method	Flare	Flare	Flare	Flare
Max Pipe Length (Ft.)	49.2	49.2	49.2	49.2
Max Elevation (Ft.)	16.4	16.4	16.4	16.4
Pipe Size (In.)	1/4 / 1/2	1/4 / 1/2	3/8 / 5/8	3/8 / 5/8
Service Port Connection (In.)	2-Jan	2-Jan	2-Jan	2-Jan
Indoor Dimensions W x D x H (In.)	31.50x11.02x7.48	35.43x11.50x8.46	42.52x13.19x9.65	48.23x12.99x9.65
Indoor Package Dimensions W x D x H (In.)	33.86x13.78x10.43	38.98x14.84x11.81	46.26x15.55x12.60	52.56x16.14x12.60
Indoor Net Weight (Lbs.)	22	31	40	44
Indoor Gross Weight (Lbs.)	26	37	51	55
Outdoor Dimensions W x D x H (In.)	31.30x10.04x21.26	33.46x11.61x23.82	35.43x12.99x32.87	35.43x12.99x32.87
Outdoor Package Dimensions W x D x H (In.)	36.22x13.19x23.43	39.17x16.34x27.17	40.55x17.32x37.80	40.55x17.32x37.80
Outdoor Net Weight (Lbs.)	73	110	143	143
Outdoor Gross Weight (Lbs.)	77	117	154	154
Refrigerant	R410A	R410A	R410A	R410A